




DATASHEET

A-DQ(ZN)B2Y OS2 8E (1x8),Fca 1750N PE black 7.1mm
G657A1



General data

Application:

For fixed installation outdoor

In cable ducts, tubes and interconnections

Mechanical installation by winch is permitted only when using force meters with recording function

Suitable for underground laying (direct buried)

Characteristics:

Outdoor cable

Resistant to oil, petrol, acid and leach

The cable diameter can vary

Allgemeine Daten

UV resistance	True
Longitudinal water blocking	True
Application	Outside
Radial water blocking	True
With strain relief	True

General data

This datasheet was created automatically on 21-05-2025 . Technical changes reserved.



DATASHEET

A-DQ(ZN)B2Y OS2 8E (1x8),Fca 1750N PE black 7.1mm
G657A1

Cable metal free	True
Colour outer sheath	black
(Halogenfree)	acc. EN 60754-1/2
Armouring	True
Blow in	False
Circuit integrity	False

Mechanical characteristics

Crush resistance	1500 N/dm
------------------	-----------

Mechanische Eigenschaften

Longitudinally watertight	3/24 m/h
---------------------------	----------

Kabelaufbau

Fiber Colours	orange
Fiber marking	Colour
Fibre category	G657.A1
Tube marking	Colour
Type of tube	Central tube
Fibre type	Single mode 9/125
Tube Ø	Up to 12 fibers: 2.9

Cable sheath

Low smoke	False
Flame-retardant	False
Oil resistant	Yes
Jacket Material	PE

Kabelmantel

Resistant to chemicals	True
------------------------	------

Umgebungsbedingungen

Temperature Range (Installation)	-5 - 50 °C
Temperature Range (Storage)	-25 - 70 °C
Temperature Range (Operation)	-25 - 60 °C

This datasheet was created automatically on 21-05-2025 . Technical changes reserved.



DATASHEET

A-DQ(ZN)B2Y OS2 8E (1x8),Fca 1750N PE black 7.1mm
G657A1

Übertragungstechnische Eigenschaften

IL max. (dB/km) 1550nm	0.4 dB/km
IL max. (dB/km) 1310nm	0.4 dB/km

Normen, Zulassungen, Zertifizierungen

Cable & Fiber	IEC/EN 60794-1
Transmission standards	IEEE 802.3 10Mbit to 100Gbit
With rodent protection	True

Standards, approvals, certifications

Cabling standards	ISO/IEC 11801
Low smoke (according to EN 61034-2)	False
Halogen free (according to EN 60754-1/2)	True

Available variants

ArtNr.	Bezeichnung	Cable Ø	Category	Number of fibres	Tensile force max.	Aufbau	Außendurchmesser ca.	Biegeradius	Gewicht
55408.1-SA	A-DQ(ZN)B2Y OS2 8E (1x8),Fca 1750N PE black 7.1mm G657A1	7.1 mm	OS2	8	1750 N	08E (1 x 8) Singlemode G.657.A1	7,1 mm	140 mm	39 kg/km

This datasheet was created automatically on 21-05-2025 . Technical changes reserved.

