

INLINE® PATCH CABLE SLIM

Cat.6A, S/FTP, TPE (LSZH) flexible, PoE, blue


The InLine® patch cable Slim, Cat.6A, S/FTP, TPE (LSZH), PoE, sets standards in terms of performance and flexibility. With S/FTP shielding at pair and cable level, it guarantees first-class signal integrity and minimises electromagnetic interference.

The TPE (LSZH) sheathing not only makes the cable extremely flexible, but also safe for use in enclosed spaces, as it does not emit any halogen-containing vapours in the event of fire. In combination with its PoE capability, it not only enables the transmission of data, but also the power supply for PoE-capable devices. Perfectly suited for professional use in offices, data centres and other business-critical environments.

- Patch cable Slim
- S/FTP - Shielded Foiled Twisted Pair
- Fulfils the Cat. 6a requirement up to 500MHz
- 2x RJ45 plugs, moulded, with latching nose protection
- Blue coloured plug for differentiation
- TPE jacket
- LSZH - Low Smoke Zero Halogen: In the event of fire, the cable does not emit any halogen-containing vapours and is therefore safer than conventional halogen-containing cables, for use in enclosed spaces
- PoE - Power over Ethernet
- Conductor material CU (copper)

Technical data	
Article height:	1,2 cm
Article width:	1,5 cm
Assignment:	1:1
Brand:	InLine®
Colour:	Blue
Conductor material:	CU (copper)
Data transmission rate:	10 Gb/s
Design:	Round cable slim
Gold plated contacts:	Yes
Operation temperature:	-20 to +75 °C
Outer diameter:	4.5 mm
Packing:	Retail
Patch cable category:	Cat.6A
PoE/PoE+/PoE++:	Yes
Sheath:	TPE (LSZH)
Shielding:	S/FTP (PiMf)
Side A:	RJ45 plug straight
Side B:	RJ45 plug straight
Signal:	Network
Storage temperature:	-20 to +75 °C
Type:	Cat.6A
Type of packaging:	InLine® bag 20103A
UL:	No
Wire size:	AWG 28


Item No.	Length	EAN
74933B	0.30 m	4043718335220
74955B	0.50 m	4043718335237
74901B	1 m	4043718335244
74914B	1.50 m	4043718335251
74902B	2 m	4043718335268
74903B	3 m	4043718335275
74905B	5 m	4043718335282
74907B	7.50 m	4043718335299
74900B	10 m	4043718335305
74915B	15 m	4043718335312
74920B	20 m	4043718335329
74925B	25 m	4043718335336
74930B	30 m	4043718335343



③	OVER MOLD	75A PVC	2
②	PLUG	RJ45 8P8C SHIELDED Plug PIN GOLD PLATED 3U", THE SHELL PLATED NICKEL, COLOUR: TRANSPARENT BLUE	2
①	CABLE	S/FTP CAT. 6A 28AWG (BC+AL-FOIL)*4P+ BRAID (AL-MG) JACKET: TPE-LSZH OD: 4.5 ± 0.2mm	1
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y

NOTE:

1. ELECTRICAL TEST: 100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel LINK TEST:
TEST LIMIT: ISO11801 Channel Class EA
3. Working temperature: -20°C ~ +75°C
Storage temperature: -20°C ~ +75°C
4. RoHS2.0 AND REACH compliant
5. Spray WORD: InLine CAT6A S/FTP 4x2x28AWG/7 TPE-LSZH
ISO11801 & EN50173 & ANSI/TIA568.2-D **CE**



Angabe der Kabellänge
Indicator of cable length

WIRING DIAGRAM




ABBILDUNG ÄHNLICH
IMAGE SIMILAR

If you have any further questions, please contact marketing@inline-info.com

www.inline-info.com/en/

Disclaimer

InLine® is a brand of INTOS ELECTRONIC AG | Siemensstraße 11 | D-35394 Gießen

Documentation © 2024 INTOS ELECTRONIC AG

All rights reserved. No part of this document may be reproduced in any form or by any means, electronic, mechanical or chemical, without the prior written permission of the publisher. It is possible that this document may still contain typographical faults or misprints.

However, the information in this document will be checked regularly and corrections will be made in the next edition. We accept no liability for errors of a technical or printing nature and their consequences. All trademarks and industrial property rights are acknowledged. Changes in the sense of technical progress can be made without prior notice. Our products, including packaging, are not toys, they may contain small parts and sharp objects.

Please keep away from children.