



# USB Type-C 9-Port Hub

Bridge Devices, Expand Connections



UH9120C



1× HDMI 4K@60Hz



1× PD 100W



1× RJ45 1 Gbps



1× SD/1× microSD 104 MB/s




USB-C/3× USB-A 5 Gbps

# Highlights



Plug & Play
For Various Operating Systems<sup>‡</sup>



## Bridge Devices, Expand Connections



**HDMI**Ultra High-Definition
Media Display



RJ45 GE
Stable Gigabit
Connection



SD/microSD

UHS-I 104 MB/s

Dual-card Reading



PD 3.0
Powerful 100W
Fast Charging



USB 3.0
5 Gbps SuperSpeed
Data Transfer



Scratch Resistant Aluminum Alloy Case

## Specifications

### Hardware

· Interface:

1× PD 3.0 100W Charging

3× USB 3.0 Type-A 5Gbps

1× USB 3.0 Type-C 5Gbps

1× HDMI 4K@60Hz

1×RJ45 1Gbps

1×SD Card Port

1×microSD Card Port

· Connector:

1× USB Type-C

· PD Input:

5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A

· USB-C Connector Input:

5V/3A

### Physical

· Dimension (W×D×H):

 $5.52 \times 1.69 \times 0.56$  in  $(140.2 \times 43 \times 14.3 \text{ mm})$ 

· Case:

Aluminum Alloy Case

· Cable:

180mm Braided Cable

· Package Contents:

1× UH9120C

1× Quick Installation Guide

### Others

Supported Systems:

Windows, Mac OS, iPad OS, iOS, Google Chrome OS, Linux OS, Nintendo OS, Android OS

· Plug & Play:

USB-C PD port, USB-C port, HDMI port, TF (microSD) card slot, SD card slot, USB-A ports, gigabit Ethernet port.\*

- \*\* The gigabit Ethernet port may require installing a driver for compatibility with certain older operating systems. Please visit our official website at www.tp-link.com to download the necessary driver for these systems:
- Windows 7/8
- Mac OS X 10.9 to 10.15
- · Certification: CE, FCC, RoHS, HDMI, BSMI
- Environment:

Operating Temperature: 0°C~40°C (32°F~104°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing



For more information, please visit

https://www.tp-link.com/products/details/?model=UH9120C V1

or scan the QR code left

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Specifications are subject to change without notice. All the brands and product names are trademarks or registered trademarks of their respective holders.

†Port transmission specifications are the testing results conducted by TP-Link laboratory. Actual transfer rate is not guaranteed and will vary as a result of device conditions and environmental factors.

†Plug and Play for Mac OS X El Capitan Version 10.11.6 and later, Windows 11/10/8.1, Linux OS, iPad OS, iOS, Android, Chrome OS, and Nintendo OS. More OS versions will be supported soon. 
§To ensure compatibility, you may need to update the hub's drivers after an OS update. You can find our latest drivers in the download center at tp-link.com/en/download-center.

©2024 TP-Link

TP-Link USB Type-C 9-Port Hub UH9120C

www.tp-link.com