



1.5m USB 3.2 Type C to C Cable, 20Gbps, 3A, Black Line

No.: 36907

USB Type C Male to C Male

Description

Entry level USB 3.2 Gen 2x2 Type C to C, 3A (60W), cable for home and small office applications
SuperSpeed USB 20Gbps - supports data transfer speeds up to 20Gbps and DisplayPort Alternate Mode
Robust PVC housing, nickel plated connectors, gold plated contacts
Triple shielded cable, corrosion resistant tinned copper conductors
10 year warranty

The Black Line USB 3.2 Type C to C cables from Lindy's Cable Lines concept are entry level connection solutions, perfect for home and small office use.

Black Line USB 3.2 Type C to C cables feature triple shielded construction with tinned copper conductors for premium performance and corrosion resistance. Nickel plated connectors and gold plated contacts maintain signal integrity and reliability.

USB bandwidths up to 20Gbps are supported for rapid transfer of large data volumes. It supports DisplayPort Alternate Mode at max. 4K 60Hz.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Black Line USB 3.2 Type C to C cables are available in the following lengths: 0.5m, 1m and 1.5m.

We have adapted the naming of our USB 3 cables to follow the updated USB specification.

USB 3.0 and USB 3.1 Gen 1 have been renamed to USB 3.2 Gen 1, supporting data transfer up to 5Gbps

USB 3.1 and USB 3.1 Gen 2 are now called USB 3.2 Gen 2, supporting data transfer rates up to 10 Gbps

USB 3.2 Gen 2x2 is a new standard, supporting data transfer rates up to 20 Gbps

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

Technical details

Connectors

Connector A: USB 3.2 Type C Male

Connector B: USB 3.2 Type C Male

Housing Material: PVC

Shielding in head shell: Copper foil
Connector Plating: Nickel
Pin Construction: Copper
Pin Plating: Gold
Dimensions [approx.] WxDxH: 11.0x25.5x7.3mm [0.43x1.00x0.29in]

Cable Construction

Length: 1.5m [4.92ft]
Standard: USB 3.2 Gen 2x2
Power Delivery: PD 2.0
Max. Power: 60W [20V 3A, Standard Power Range [SPR]]
Colour: Black
Type: Round
Jacket Diameter: 4.5mm [0.18in]
Jacket Material: PVC
Conductor Material: Tinned Copper
Conductor Gauge Power: 24AWG
Conductor Gauge Data: 32AWG
Shielding: Tinned Copper Braid 86%

Specifications

Supported Bandwidth: 20Gbps
Maximum Resolution: 4K 4096x2160@60Hz
Nominal Attenuation: 0.5Mhz _ 15Ghz < 40dB
Minimum Bend Radius: 45mm [1.77in]
Operating Temperature: 0°C - 40°C [32°F - 104°F]
Storage Temperature: 0°C - 70°C [32°F - 158°F]

Miscellaneous

Packaging Type: Polybag
Warranty (Years): 10
Product Compliance: RoHS, REACH, California Proposition 65 & UL

Purchasing Information

No.36907
EAN: 4002888369077

This product is also available in other lengths

36905 - 0.5m [1.64ft]
36906 - 1m [3.28ft]
36907 - 1.5m [4.92ft]