



INLINE® PATCH CABLE FLAT


U/FTP, Cat.6A, TPE halogen-free, grey

- flat patch cable
- U/FTP Shielded: In pairs in metal foil (PIMf)
- fulfils the Cat.6 A requirements up to 500MHz
- Four core pairs, twisted
- solid copper strands
- 1: 1 assignment, colour-coded according to EIA/TIA-568B
- 2x RJ45 plug, moulded, with latching lug protection
- Blue coloured plug for differentiation
- Halogen-free TPE jacket
- flexible and easy to install
- in a resealable PE bag with EAN code


Item No.	Length	EAN
75712	0,25 m	4043718294862
75713	0,30 m	4043718294879
75755	0,50 m	4043718294886
75701	1 m	4043718294893
75714	1,50 m	4043718294909
75702	2 m	4043718294916
75703	3 m	4043718294923
75705	5 m	4043718294930
75707	7,50 m	4043718294947
75700	10 m	4043718294954
75715	15 m	4043718294961
75720	20 m	4043718294978

Technical Data	
Article height:	1.6 cm
Article width:	1.2 cm
Assignment:	1:1
Conductor material:	CU (copper)
Data transmission rate:	10 Gb/s
Design:	Flat cable
Diameter:	AWG 32
Max. supported PoE standard:	802.3af
Max. supported data transfer rate:	10 Gb/s
Max. supported power:	15.4 W
Outer diameter:	2.0x6.5 mm
Packing:	Retail
Patch cable category:	Cat.6A
PoE/PoE+/PoE++:	No
Sheath:	TPE
Shielding:	U/FTP
Side A:	RJ45 plug straight
Side B:	RJ45 plug straight
Signal:	Network
Type:	Cat.6A
UL:	No

Wire pairs used for power transmission: 1236 or 4578, the specific method used is determined by the PSE (Power Sourcing Equipment)



PIN OUT



CN1 (568B)		CN2 (568B)	
WHITE-ORANGE 1	1	WHITE-ORANGE 1	1
ORANGE 2	2	ORANGE 2	2
WHITE-GREEN 3	3	WHITE-GREEN 3	3
GREEN 6	6	GREEN 6	6
BLUE 4	4	BLUE 4	4
WHITE-BLUE 5	5	WHITE-BLUE 5	5
WHITE-BROWN 7	7	WHITE-BROWN 7	7
BROWN 8	8	BROWN 8	8
SHELL		SHELL	

1. 100% open short & miss wire test;
2. Fluke channel test:
ISO11801 channel class Ea
3. RoHS2.0 AND REACH compliant
4. PRINT WORD: InLine CAT. 6A U/FTP FLAT TPE 500MHz
4x2x32AWG/7 ISO11801 & EN50173 & ANSI/TIA568C.2
5. Operating temperature: -20°C ~ +75°C

③	Over mold	75A PVC (Same color as wire)	2
②	Plug	RJ45 8P8C'S SHIELDED THE SHELL PLATED NICKEL, PIN GOLD PLATED 3u" TRANSPARENT Blue	2
①	CABLE	CAT. 6A U/FTP (32AWG BC*1P+AL-FOIL)*4PAIRS+DRAIN (AL-MG)+JACKET: Super Soft Halogenfree TPE (IEC 60754-2), OD: 6.5*2.0 ± 0.2mm	1

If you have any further questions, please contact marketing@inline-info.com

www.inline-info.com/en/

Disclaimer

InLine® is a brand of INTOS ELECTRONIC AG | Siemensstraße 11 | D-35394 Gießen

Documentation © 2026 INTOS ELECTRONIC AG

All rights reserved. No part of this document may be reproduced in any form or by any means, electronic, mechanical or chemical, without the prior written permission of the publisher. It is possible that this document may still contain typographical faults or misprints.

However, the information in this document will be checked regularly and corrections will be made in the next edition. We accept no liability for errors of a technical or printing nature and their consequences. All trademarks and industrial property rights are acknowledged. Changes in the sense of technical progress can be made without prior notice. Our products, including packaging, are not toys, they may contain small parts and sharp objects.

Please keep away from children.