


DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 1m



General data

RJ45 flat patch cable Cat.6A U/FTP PVC

The Cat.6A (TIA) patch cable has gold-plated contacts and meets the requirements for 10Gbit Ethernet.

Technical product features

- Cat.6A (TIA)
- U/FTP cable with AWG30/7
- Sheath material made of polyvinyl chloride (PVC)
- Plug connection: RJ45 to RJ45
- With locking lever protection
- Has gold-plated contacts

The sheath of the shielded patch cable is made of polyvinyl chloride (PVC) material. In addition, the cable offers the option of power supply via PoE+ according to IEEE802.3at and PoE according to IEEE802.3af.

This datasheet was created automatically on 17-05-2025 . Technical changes reserved.

DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 1m

The assignment of the particularly short RJ45 plugs is 1:1 and follows TIA/EIA 568B. Suitable for the temperature range -20 - 55 °C.

The Ethernet cable has a copper conductor material and is ideal for applications in structured building cabling, industrial Ethernet and data centers. This achieves a bandwidth of 500 MHz.

Allgemeine Daten

Suitable for degree of protection (IP)	IP20
Jacket Material	Polyvinylchlorid (PVC)
AWG-size	30/7
Length imprint	False
Colour anti-kink sleeve	black

General data

Connector type	RJ45 short version
Colour outer sheath	black
Fire retardant version	False
Pin assignment	1:1
Locking lever	True
Model	Shielded
Bending radius	>20 mm
Contacts	Gold plated
Allocation	acc. TIA/EIA 568B
Cable type	U/FTP
Area of Application	Industrial Ethernet
Anti-kink sleeve	plugged in
Category	6A (TIA)
(Halogenfree)	False

Mechanical characteristics

Conductive shield	Selected shield contact
Mating cycles	2000

Cable construction

Conductor Material	Copper
--------------------	--------

Kabelaufbau

Type of connector connection 2	RJ45 8(8)
--------------------------------	-----------

This datasheet was created automatically on 17-05-2025 . Technical changes reserved.

DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 1m

Type of connector connection 1	RJ45 8(8)
Cable construction	4x2

Cable sheath

Oil resistant (according to EN 60811-404)	False
Silicone-free	True
Outer diameter of the cable	7.0*2.2 mm

Kabelmantel

Printing	SLIM PATCHCABLE U/FTP CAT.6A ***10GB*** www.efb-elektronik.de
----------	--

Environmental conditions

Temperature range	-20 - 55 °C
-------------------	-------------

Electrical characteristics

Loop resistance	752 Ω/km
Impedance	100 ±15 Ω
Conductor resistance DC	376 Ω/km
Resistance unbalance	< 4 %
POE class	PoE+ acc. to IEEE802.3at
Operating-/ tempering voltage	max. 50 V DC
Current Rating	max. 1 A
NVP value	76 %
Insulation Resistance	100 MΩ

Elektrische Eigenschaften

Test voltage	1000 (V DC, 1min) core/core und core/screen
--------------	---

Übertragungstechnische Eigenschaften

Bandwidth	500MHz
-----------	--------

Standards, approvals, certifications

Cabling Standard	EN50173
Oil resistant (acc. EN 60811-2-1)	False
Connector	IEC 60603-7-51

This datasheet was created automatically on 17-05-2025 . Technical changes reserved.



DATASHEET

RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 1m

Available variants

ArtNr.	Bezeichnung	Length	Längentoleranz
K5545SW.0,15	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 0.15m	0.15 m	±5 %
K5545SW.0,25	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 0,25m	0.25 m	±5 %
K5545SW.0,5	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 0,5m	0.5 m	±5 %
K5545SW.1	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 1m	1.0 m	±5 %
K5545SW.1,5	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 1,5m	1.5 m	±5 %
K5545SW.2	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 2m	2.0 m	±5 %
K5545SW.3	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 3m	3.0 m	±5 %
K5545SW.5	RJ45 Flat Patch Cord Cat.6A U/FTP PVC black 5m	5.0 m	±5 %

This datasheet was created automatically on 17-05-2025 . Technical changes reserved.

