



## 2m USB 3.2 Type A to B Cable, 5Gbps, Anthra Line

No.: 36742

USB Type A Male to B Male

### Description

Professional choice USB 3.2 Gen 1 Type A to B cable for commercial and high performance AV and IT installations  
SuperSpeed USB - supports data transfer speeds up to 5Gbps [USB 3.2 Gen 1, USB 3.1 Gen 1, USB 3.0]  
Robust PVC housing, gold plated connectors and contacts  
Triple shielded cable, corrosion resistant tinned copper conductors  
10 year warranty

The Anthra Line USB 3.2 Type A to B cables from Lindy's Cable Lines concept are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 3.2 cables are premium connections that feature triple shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

USB bandwidths up to 5Gbps are supported for rapid transfer of large data volumes.

Anthra Line USB 3.2 Type A to B cables are available in the following lengths: 0.5m, 1m, 2m, 3m and 5m.

We have adapted the naming of our USB 3 cables to follow the updated USB specification.

USB 3.0 and USB 3.1 Gen 1 have been renamed to USB 3.2 Gen 1, supporting data transfer up to 5Gbps

USB 3.1 and USB 3.1 Gen 2 are now called USB 3.2 Gen 2, supporting data transfer rates up to 10 Gbps

USB 3.2 Gen 2x2 is a new standard, supporting data transfer rates up to 20 Gbps

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

### Technical details

#### Connectors

Connector A: USB 3.2 Type A Male

Connector B: USB 3.2 Type B Male

Housing Material: PVC

Shielding in head shell: -

Connector Plating: Gold Plated

Pin Construction: Brass

Pin Plating: Gold Plated

Dimensions [approx.] WxDxH:

A: 15.5x35x7.8mm [0.61x1.38x0.31in]

B: 12.2x35x13.5mm (0.48x1.38x0.53in)

#### **Cable Construction**

Length: 2m (6.56ft)

Standard: USB 3.2 Gen 1 (USB 3.1 Gen 1, USB 3.0)

Power Delivery: -

Colour: Black

Type: Round

Jacket Diameter: 5.5mm (0.22in)

Jacket Material: PVC

Conductor Material: Tinned Copper

Conductor Gauge Power: 24AWG

Conductor Gauge Data: 28AWG

Shielding: Aluminium Magnesium Braid 80%

#### **Specifications**

Supported Bandwidth: 5Gbps

Maximum Resolution: -

Nominal Attenuation: 0.5MHz - 7.5GHz < 25dB

Minimum Bend Radius: 48mm (1.89in)

Operating Temperature: 0°C - 40°C (32°F - 104°F)

Storage Temperature: 0°C - 70°C (32°F - 158°F)

#### **Miscellaneous**

Packaging Type: Polybag

Warranty (Years): 10

Product Compliance: RoHS, REACH, California Proposition 65 & UL

#### **Purchasing Information**

No. 36742

EAN: 4002888367424

#### **This product is also available in other lengths**

36740 - 0.5m (1.64ft)

36741 - 1m (3.28ft)

36742 - 2m (6.56ft)

36743 - 3m (9.84ft)

36744 - 5m (16.40ft)