



300m Cat.6 VGA, USB & PS/2 KVM Extender Combo

No.: 39378

Extend VGA, USB or PS/2 over a Cat.6 cable

Description

Extends VGA, USB and PS/2 up to 300m using a single Cat.6 cable

Supports VGA resolutions up to 1920x1200

Dual console operation - control your computer / KVM Switch from both local and remote locations

Easy, user friendly installation - no software required

2 year warranty

The Lindy Cat.6 VGA, USB & PS/2 KVM Extender allows users to control a source device such as a PC from a single keyboard, mouse and display up to 300m using a Cat.5e/6 RJ45 cable. Supports analogue resolutions up to 1920x1200 with VGA ports, ideal for managing a PC or workstation from very long distances. The Extender features PC & console ports on the transmitter to connect additional display, keyboard and mouse for local control and console & PC ports on the receiver to connect an additional PC on the remote console side. In both units you can either connect USB or PS/2 keyboard and mouse and PCs using the KVM cables included. It's also possible to connect a second source on the receiver unit and control it pushing the switching button on the front panel or via hotkey. Via OSD menu users can adjust video signal, EDID, enable password protection and change hotkeys.

This extender provides a simple plug & play installation, no additional drivers required, great for both professional and first time users.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.

Technical details

Specifications

AV Interface: VGA

Console Interface: USB, PS/2

Interfaces Standard: VGA, USB (HID), PS/2

Supported Bandwidth: 350MHz

Maximum Distance: 300m (984.24ft)

Maximum Resolution: 1920x1200@60Hz

HDCP Support: -

Supported Audio: -

Separate Audio Ports: -

Transmission Protocol: -

Transmission Medium: Cat.5e / 6

Laser Class (only for Fibre): -

Wavelength (only for Fibre): -

Special Features: OSD menu, local console switching, remote PC switching

Connectors

Transmitter KVM Interfaces: Console ports: VGA (Female), 2 x USB Type A (Female), 2 x PS/2 (Female)

PC Port: VGA (Female)

Transmitter Extension Port: 1 x RJ45

Receiver Console Interface: Console ports: VGA (Female), 2 x USB Type A (Female), 2 x PS/2 (Female)

PC Port: VGA (Female)

Receiver Extension Port: 1 x RJ45

Bi-directional Ports: -

Other Interfaces: USB Type B (Female) for upgrade

Power: 5.5/2.5mm DC socket

Physical Properties

Dimensions (approx.) WxDxH: 130x70x28mm (5.12x2.76x1.1in) (each unit)

Housing Material: Metal

Net Weight: 0.3kg (0.66lb) (each unit)

Operating Temperature : 0°C - 40°C (32°F - 104°F)

Storage Temperature: -20°C - 60°C (-4°F - 140°F)

Humidity: 0 - 90% RH (non-condensing)

Power Requirements: 5VDC 3A

Colour: Black

Miscellaneous

Packaging Type: Carton Box

Packaging Dimensions: 220x150x190mm (8.66x5.91x7.48in)

Gross Weight: 1.79kg (3.95lb)

Warranty (Years): 2

Certification: CE, FCC, RoHS & REACH

Package Content

Transmitter Unit

Receiver Unit

2 x 3-in-1 KVM cable, 1.2m

2 x USB to PS/2 adapter

1 x USB Type A/B cable, 1.2m

2 x Multi-Country Power Supply (EU, UK, US, AUS)

Lindy Manual

Purchasing Information

No.: 39378

EAN: 4002888393782